## **When Quality Matter**




## Wire Rope

Advance Oil field supplies a is one of largest stock holder of wire ropes in UAE. We sales some of the world's leading brands such as Bridon & Kiswire. Some features are as below.

- Sizes From 3mm to 80mm
- Rotating & non rotating wire ropes
- Constructions 6X19, 6X25, 6X36, 19X7, 35X7
- Galvanized & un-Galvanized
- left hand lay & right hand lay
- Core IWRC, FC and WSC

Please feel free to contact us for further details











Rope Core
A small wire rope is used as
the core. Excellent crush and
distortion resistance with longer
fatigue life, and high breaking

## Wire Rope Sling

## Wire Rope Slings-Types



Wire Rope Slings- End fitting



| CAPACITY CHART FOR WIRE ROPE SLING 6 x19 6x36 STEEL CORE |        |         |                |         |                  |         |
|--|--------|---------|----------------|---------|------------------|---------|
| mm   | inches | One Leg | Two Leg Slings |         | Three & Four Leg |         |
| Angle  |        | 0°      | 0°-45°         | 45°-60° | 0°-45°           | 45°-60° |
| Safety Factor  |        | 1       | 1.4            | 1       | 2.1              | 2.1     |
| 10   | 3/8    | 1.15    | 1.60           | 1.15    | 2.40             | 1.70    |
| 13   | 1/2    | 2.00    | 2.80           | 2.00    | 4.15             | 3.00    |
| 16   | 5/8    | 3.00    | 4.20           | 3.00    | 6.30             | 4.50    |
| 19   | 3/4    | 4.60    | 6.50           | 4.60    | 9.80             | 6.90    |
| 22   | 7/8    | 5.65    | 7.80           | 5.65    | 11.8             | 8.40    |
| 26   | 1      | 7.80    | 11.0           | 7.80    | 16.5             | 11.5    |
| 28   | 1.1/8  | 9.00    | 12.5           | 9.00    | 19.0             | 13.5    |
| 32   | 1.1/4  | 11.8    | 16.5           | 11.8    | 25.0             | 17.5    |
| 36   | 1.3/8  | 15.0    | 21.0           | 15.0    | 31.5             | 22.5    |
| 40   | 1.1/2  | 18.5    | 26.0           | 18.5    | 39.0             | 28.0    |
| 44   | 1.3/4  | 22.5    | 31.5           | 22.5    | 47.0             | 33.5    |
| 52   | 2      | 31.5    | 44.0           | 31.5    | 66.0             | 47.0    |

